



Specification: Slim self-contained emergency LED exit sign box. Viewing distance 34m. Constant emergency light (90lm) for 3 hours. Low stand-by power consumption. Self-test versions and remote controls available. Lithium battery as standard. Maintained or non-maintained configurations. Suitable for indoor applications such as educational and offices buildings.



Key Features


- Test button integrated
- Viewing distance 34m
- Fast battery re-charge (8 hrs)*
- "UP" arrow included
- Low stand-by power consumption (0.5 W)**
- Remote control available

* First battery charge takes up to 16 hours

** Non-maintained mode only

SPEEDY Emergency Exit Sign Box

Part number	Description	Testing facility	Operating temperature	Net weight
BXA34-DL	Exit sign box 1.5W 34m viewing distance DALI-2 addressable	DALI-2 Addressable with Z10 certified PCB LPD1-DL	0°C ~ 40°C	1.15 kg
BXA-D	Exit sign metal box DOWN ARROW legend	-		0.14 kg
BXA-R	Exit sign metal box RIGHT ARROW legend	-		
BXA-L	Exit sign metal box LEFT ARROW legend	-		



SPEEDY Emergency Exit Sign Box

Technical information

Input voltage/frequency	220-240V AC 50Hz
Power consumption	
Maintained	5W(Max.*)
Non-maintained	3W(Max.*), 0.5W(standby)
LEDs Lifetime (L-70)	50,000h
Viewing distance	34m
Discharge duration	3 hours
Wh (maintained standby)	3
Wh (non-maintained standby)	0.5
Charge duration	up to 8hrs (first charge up to 16hrs)
Test facility	DL
IP rating	IP20
IK rating	IK07
Insulation class	I
Operation temp.	0~40°C
Storage temp.	0~50°C

Light Source

Brand	Everlight
Quantity	24 pcs
CCT	5700K
CRI	>80

* Power consumption only during charging mode

INSTALLATION NOTES

- Wall mount
- BESA entry template on rear
- Cable entry to sides, top and rear (20mm cut-outs)
- Terminal block takes wires up to 4 x 1.5mm²

TESTING FACILITIES

DL (DALI-2 addressable)	This luminaire is DALI-2 compatible and requires additional software and hardware to program and control it. Testing should be carried out in accordance to BS EN 50172:2004.
-------------------------	---

Materials

Luminaire housing	Steel
Luminaire diffuser	Polycarbonate
Luminaire bracket	N.A.
Luminaire legend	Polycarbonate
Luminaire screws	Zinc plated steel
Finish	Matt
Colour	White
Battery type	Li-Ion 3.6V 2500mAh

Logistic information

Product dimensions (L x W x D)mm	392.6 x 41.2 x 196.2 mm
Product Net weight (kg)	1.15 kg
Box dimensions (L x W x D)mm	410 x 205 x 45 mm
Gross weight (kg)	1.25 kg
Quantity of outer carton	12 pcs
Outer carton dimensions(L x W x D)mm	424 x 280 x 427 mm
Outer carton gross weight (kg)	15.5 kg
Quantity per Euro pallet (1200 x 800)	288 pcs
Pallet weight (kg)	10 kg

Certification

Safety standard	BS EN 60598-2-22
Certified by	DEKRA
UKCA /CE Mark	Yes
Factory QMS	ISO9001