


Specification: DALI-2 certified, addressable, stand-alone self-contained emergency LED downlight. Corridor or Open Area lens integrated. Constant emergency light (1.5W/190lm & 200lm) for 3 hours. Low stand-by power consumption (0.5W). Self-test versions and remote controls available. Lithium battery as standard. Non-maintained configuration. Ceiling surface mount. Suitable for open area and corridor indoor applications.



Key Features

- Integrated test button
- Low stand-by power consumption (0.5 W)
- Fast battery re-charge (8 hours)*
- Open area, corridor and spot lens options
- Remote control available

* First battery charge takes up to 16 hours

VISUAL Emergency Downlight

Part number *	Description	Testing facility	Remote control part number *	Operating temperature	Net weight
DLB1.5-C-DL	Ceiling mounted LED downlight NM 1.5W 190lm corridor	DALI-2 Addressable with Z10 certified PCB LPD1-DL	-	0°C ~ 40°C	0.27 kg
DLB1.5-OA2-DL	Ceiling mounted LED downlight NM 1.5W 200lm corridor	DALI-2 Addressable with Z10 certified PCB LPD1-DL	-		

*For Black option add -BLK to part number shown

VISUAL Emergency Downlight

Technical information

Input voltage/frequency	220-240V AC 50Hz
Power consumption	
Maintained	N.A.
Non-maintained	3W(Max.*) 0.5W(standby)
Lumen output	
On mains voltage	N.A.
On emergency mode	190lm / 200lm
LEDs Lifetime (L-70)	50,000h
Discharge duration	3 hours
Wh (non-maintained standby)	0.5
Charge duration	up to 8hrs (first charge up to 16hrs)
Test facility	DALI-2
IP rate	IP20
IK rate	IK06
Insulation class	II
Operation temp.	0~40°C
Storage temp.	0~50°C

Light Source

Brand	Luminus
Quantity	1 pcs
CCT	4000K
CRI	>80

* Power consumption only during charging mode

Installation Notes

- Surface ceiling mount
- Cable entry to side (20mm cut-out) and rear
- Screwless terminal block (L, N, earth loop in/out)
- Terminal block takes wires up to 3 x 2.5mm²

TESTING FACILITIES

DL (DALI-2 Addressable)

This luminaire is DALI-2 compatible and requires additional software and hardware to program DL (DALI-2 Addressable) and control it. Testing should be carried out in accordance to BS EN 50172:2004.

Materials

Luminaire housing	Polycarbonate
Luminaire diffuser	Polycarbonate
Luminaire bracket	Polycarbonate
Luminaire legend	N.A.
Luminaire screws	Nickel Steel
Finish	Matt
Colour	White / Black
Battery type	Li-Ion 3.6V 2500mAh

Logistic information

Product dimensions (L x W x D)mm	R75 x 40 mm
Product Net weight (kg)	0.27kg
Box dimensions (L x W x D)mm	160 x 154 x 50 mm
Gross weight (kg)	0.35kg
Quantity of outer carton	28 pc's
Outer carton dimensions(L x W x D)mm	360 x 336 x 327 mm
Outer carton gross weight (kg)	11.5kg
Quantity per Euro pallet (1200 x 800)	672 pc's
Pallet weight (kg)	10 kg

Certification

Safety standard	BS EN 60598-2-22
Certified by	DEKRA
UKCA / CE mark	Yes
Factory QMS	ISO9001